

LS (17 mm) YASSI BORULARIMIZIN UZATMA MESAFESİ 1 bar basınç ve düz arazide

| Debi Farklılığı | 20cm damla aralığı | | | 25cm damla aralığı | | | 30cm damla aralığı | | | 40cm damla aralığı | | | 50cm damla aralığı | | | 60cm damla aralığı | | | 100cm damla aralığı | | |
|-----------------|--------------------|---------|---------|--------------------|---------|---------|--------------------|---------|---------|--------------------|---------|---------|--------------------|---------|---------|--------------------|---------|---------|---------------------|---------|---------|
| | 1.3 l/s | 1.6 l/s | 2.6 l/s | 1.3 l/s | 1.6 l/s | 2.6 l/s | 1.3 l/s | 1.6 l/s | 2.6 l/s | 1.3 l/s | 1.6 l/s | 2.6 l/s | 1.3 l/s | 1.6 l/s | 2.6 l/s | 1.3 l/s | 1.6 l/s | 2.6 l/s | 1.3 l/s | 1.6 l/s | 2.6 l/s |
| %5 | 70 | 65 | 45 | 110 | 104 | 72 | 120 | 110 | 82 | 160 | 153 | 106 | 170 | 164 | 119 | 210 | 199 | 135 | 250 | 234 | 192 |
| %7.5 | 80 | 70 | 55 | 120 | 116 | 81 | 130 | 120 | 95 | 180 | 170 | 118 | 195 | 185 | 134 | 230 | 223 | 152 | 290 | 270 | 217 |
| %10 | 100 | 80 | 60 | 135 | 124 | 85 | 140 | 130 | 100 | 190 | 182 | 124 | 210 | 198 | 141 | 240 | 238 | 161 | 300 | 292 | 230 |
| %15 | 105 | 95 | 70 | 145 | 137 | 91 | 157 | 150 | 110 | 205 | 200 | 137 | 230 | 220 | 156 | 270 | 264 | 178 | 345 | 332 | 256 |

LSG (22.2 mm) YASSI BORULARIMIZIN UZATMA MESAFESİ 1 bar basınç ve düz arazide

| Debi Farklılığı | 20cm damla aralığı | | | 25cm damla aralığı | | | 30cm damla aralığı | | | 40cm damla aralığı | | | 50cm damla aralığı | | | 60cm damla aralığı | | | 100cm damla aralığı | | |
|-----------------|--------------------|---------|---------|--------------------|---------|---------|--------------------|---------|---------|--------------------|---------|---------|--------------------|---------|---------|--------------------|---------|---------|---------------------|---------|---------|
| | 1.3 l/s | 1.6 l/s | 2.6 l/s | 1.3 l/s | 1.6 l/s | 2.6 l/s | 1.3 l/s | 1.6 l/s | 2.6 l/s | 1.3 l/s | 1.6 l/s | 2.6 l/s | 1.3 l/s | 1.6 l/s | 2.6 l/s | 1.3 l/s | 1.6 l/s | 2.6 l/s | 1.3 l/s | 1.6 l/s | 2.6 l/s |
| %5 | 70 | 100 | 70 | 150 | 135 | 95 | 175 | 140 | 104 | 200 | 148 | 141 | 220 | 201 | 161 | 245 | 226 | 180 | 390 | 273 | 206 |
| %7.5 | 110 | 115 | 80 | 170 | 150 | 104 | 200 | 158 | 117 | 230 | 200 | 155 | 280 | 227 | 179 | 280 | 256 | 200 | 410 | 311 | 236 |
| %10 | 130 | 145 | 85 | 182 | 167 | 120 | 210 | 172 | 127 | 240 | 216 | 166 | 300 | 247 | 194 | 320 | 278 | 210 | 420 | 341 | 258 |
| %15 | 165 | 175 | 105 | 205 | 185 | 135 | 220 | 192 | 143 | 260 | 240 | 180 | 330 | 278 | 210 | 340 | 313 | 240 | 470 | 390 | 300 |

17 mm YASSI BORULARIMIZIN KARAKTERİSTİKLERİ

| Boru Cinsi/Çapı Damlatıcı Arası | İşletme Basıncı ATM | Damlatıcı Debisi Lt/Saat | Boru Çapı (mm) | | Et Kalınlığı (mm) | Max. İşletme Basıncı ATM | Filtre | Kangal Uzunluğu (m) | Tıra Giren Miktar (km) | Bir Kamyonla Giren Miktar (km) |
|---------------------------------|---------------------|--------------------------|----------------|------|-------------------|--------------------------|--------|---------------------|------------------------|--------------------------------|
| | | | İç | Dış | | | | | | |
| LS-6/0.8 | 1.0 | 0.81 | 16.1 | 16.4 | 0.15 | 1.3 | 120 | 2500 | 1600 | 800 |
| LS-6/1.3 | 1.0 | 1.24 | 16.1 | 16.4 | 0.15 | 1.3 | 120 | 2500 | 1600 | 800 |
| LS-6/1.6 | 1.0 | 1.62 | 16.1 | 16.4 | 0.15 | 1.3 | 120 | 2500 | 1600 | 800 |
| LS-6/2.6 | 1.0 | 2.50 | 16.1 | 16.4 | 0.15 | 1.3 | 120 | 2500 | 1600 | 800 |
| LS-6/3.8 | 1.0 | 4.0 | 16.1 | 16.4 | 0.15 | 1.3 | 120 | 2500 | 1600 | 800 |
| LS-10/0.8 | 1.0 | 0.79 | 16.1 | 16.5 | 0.25 | 1.5 | 120 | 2000 | 1280 | 640 |
| LS-10/1.3 | 1.0 | 1.2 | 16.1 | 16.5 | 0.25 | 1.5 | 120 | 2000 | 1280 | 640 |
| LS-10/1.6 | 1.0 | 1.55 | 16.1 | 16.5 | 0.25 | 1.5 | 120 | 2000 | 1280 | 640 |
| LS-10/2.6 | 1.0 | 2.25 | 16.1 | 16.5 | 0.25 | 1.5 | 120 | 2000 | 1280 | 640 |
| LS-10/3.8 | 1.0 | 3.8 | 16.1 | 16.5 | 0.25 | 1.5 | 120 | 2000 | 1280 | 640 |
| LS-12/0.8 | 1.0 | 0.75 | 16.1 | 16.7 | 0.3 | 1.5 | 120 | 1500 | 960 | 480 |
| LS-12/1.3 | 1.0 | 1.2 | 16.1 | 16.7 | 0.3 | 1.5 | 120 | 1500 | 960 | 480 |
| LS-12/1.6 | 1.0 | 1.55 | 16.1 | 16.7 | 0.3 | 1.5 | 120 | 1500 | 960 | 480 |
| LS-12/2.6 | 1.0 | 2.25 | 16.1 | 16.7 | 0.3 | 1.5 | 120 | 1500 | 960 | 480 |
| LS-12/3.8 | 1.0 | 3.8 | 16.1 | 16.7 | 0.3 | 1.5 | 120 | 1500 | 960 | 480 |
| LS-18/0.8 | 1.0 | 0.79 | 16.1 | 17.0 | 0.45 | 2.0 | 120 | 1000 | 640 | 320 |
| LS-18/1.3 | 1.0 | 1.2 | 16.1 | 17.0 | 0.45 | 2.0 | 120 | 1000 | 640 | 320 |
| LS-18/1.6 | 1.0 | 1.55 | 16.1 | 17.0 | 0.45 | 2.0 | 120 | 1000 | 640 | 320 |
| LS-18/2.6 | 1.0 | 2.25 | 16.1 | 17.0 | 0.45 | 2.0 | 120 | 1000 | 640 | 320 |
| LS-18/3.8 | 1.0 | 3.8 | 16.1 | 17.0 | 0.45 | 2.0 | 120 | 1000 | 640 | 320 |
| LS-24/0.8 | 1.0 | 0.79 | 16.1 | 17.3 | 0.6 | 2.5 | 120 | 750 | 480 | 240 |
| LS-24/1.3 | 1.0 | 1.2 | 16.1 | 17.3 | 0.6 | 2.5 | 120 | 750 | 480 | 240 |
| LS-24/1.6 | 1.0 | 1.55 | 16.1 | 17.3 | 0.6 | 2.5 | 120 | 750 | 480 | 240 |
| LS-24/2.6 | 1.0 | 2.25 | 16.1 | 17.3 | 0.6 | 2.5 | 120 | 750 | 480 | 240 |
| LS-24/3.8 | 1.0 | 3.8 | 16.1 | 17.3 | 0.6 | 2.5 | 120 | 750 | 480 | 240 |
| LS-36/0.8 | 1.0 | 0.75 | 16.1 | 17.9 | 0.6 | 3.0 | 120 | 450 | 288 | 144 |
| LS-36/1.3 | 1.0 | 1.2 | 16.1 | 17.9 | 0.9 | 3.0 | 120 | 450 | 288 | 144 |
| LS-36/1.6 | 1.0 | 1.55 | 16.1 | 17.9 | 0.9 | 3.0 | 120 | 450 | 288 | 144 |
| LS-36/2.6 | 1.0 | 2.25 | 16.1 | 17.9 | 0.9 | 3.0 | 120 | 450 | 288 | 144 |
| LS-36/3.8 | 1.0 | 3.8 | 16.1 | 17.9 | 0.9 | 3.0 | 120 | 450 | 288 | 144 |

**22 mm YASSI BORULARIMIZIN KARAKTERİSTİKLERİ**

| Boru Cinsi/Çapı Damlatıcı Arası | İşletme Basıncı ATM | Damlatıcı Debisi Lt/Saat | Boru Çapı (mm) | | Et Kalınlığı (mm) | Max. İşletme Basıncı ATM | Filtre | Kangal Uzunluğu (m) | Tıra Giren Miktar (km) | Bir Kamyonla Giren Miktar (km) |
|---------------------------------|---------------------|--------------------------|----------------|------|-------------------|--------------------------|--------|---------------------|------------------------|--------------------------------|
| | | | İç | Dış | | | | | | |
| LSG-10/0.8 | 1.0 | 0.79 | 22.2 | 22.7 | 0.25 | 1.3 | 120 | 1400 | 896 | 448 |
| LSG-10/1.3 | 1.0 | 1.2 | 22.2 | 22.7 | 0.25 | 1.3 | 120 | 1400 | 896 | 448 |
| LSG-10/1.6 | 1.0 | 1.55 | 22.2 | 22.7 | 0.25 | 1.3 | 120 | 1400 | 896 | 448 |
| LSG-10/2.6 | 1.0 | 2.25 | 22.2 | 22.7 | 0.25 | 1.3 | 120 | 1400 | 896 | 448 |
| LSG-10/3.8 | 1.0 | 3.8 | 22.2 | 22.7 | 0.25 | 1.3 | 120 | 1400 | 896 | 448 |
| LSG-12/0.8 | 1.0 | 0.75 | 22.2 | 22.8 | 0.3 | 1.4 | 120 | 1300 | 832 | 416 |
| LSG-12/1.3 | 1.0 | 1.2 | 22.2 | 22.8 | 0.3 | 1.4 | 120 | 1300 | 832 | 416 |
| LSG-12/1.6 | 1.0 | 1.55 | 22.2 | 22.8 | 0.3 | 1.4 | 120 | 1300 | 832 | 416 |
| LSG-12/2.6 | 1.0 | 2.25 | 22.2 | 22.8 | 0.3 | 1.4 | 120 | 1300 | 832 | 416 |
| LSG-12/3.8 | 1.0 | 3.8 | 22.2 | 22.8 | 0.3 | 1.4 | 120 | 1300 | 832 | 416 |
| LSG-15/0.8 | 1.0 | 0.81 | 22.2 | 22.9 | 0.37 | 1.7 | 120 | 1000 | 704 | 352 |
| LSG-15/1.3 | 1.0 | 1.24 | 22.2 | 22.9 | 0.37 | 1.7 | 120 | 1000 | 704 | 352 |
| LSG-15/1.6 | 1.0 | 1.55 | 22.2 | 22.9 | 0.37 | 1.7 | 120 | 1000 | 704 | 352 |
| LSG-15/2.6 | 1.0 | 2.4 | 22.2 | 22.9 | 0.37 | 1.7 | 120 | 1000 | 704 | 352 |
| LSG-15/3.8 | 1.0 | 3.8 | 22.2 | 22.9 | 0.37 | 1.7 | 120 | 1000 | 704 | 352 |
| LSG-24/1.3 | 1.0 | 1.24 | 22.2 | 22.3 | 0.6 | 2.0 | 450 | 288 | 144 | 144 |
| LSG-24/2.6 | 1.0 | 2.25 | 22.2 | 22.3 | 0.6 | 2.0 | 450 | 288 | 144 | 144 |
| LSG-36/1.6 | 1.0 | 1.24 | 22.2 | 24.0 | 0.9 | 2.0 | 300 | 192 | 96 | 96 |
| LSG-36/2.6 | 1.0 | 2.25 | 22.2 | 24.0 | 0.9 | 2.0 | 300 | 192 | 96 | 96 |

**LS (17 mm) ve LSG (22 mm) YASSI BORULARIMIZIN UZATMA MESAFESİ (metre)**

Sıfır eğim %10 debi varyasyonu

| Debi Lt/saat | Damlalık Mesafesi (cm) | | | | | | | |
|---------------------|------------------------|------|------|------|------|------|------|-------|
| | 20cm | 25cm | 30cm | 40cm | 50cm | 60cm | 80cm | 100cm |
| LS-0.8 - LSG-10/0.8 | 125 | 150 | 170 | 205 | 240 | 270 | 330 | 380 |
| LS-1.3 - LSG-10/1.3 | 95 | 135 | 145 | 190 | 210 | 240 | 290 | 300 |
| LS-1.6 - LSG-10/1.6 | 80 | 124 | 140 | 182 | 198 | 238 | 280 | 292 |
| LS-2.6 - LSG-10/2.6 | 60 | 85 | 94 | 124 | 141 | 161 | 200 | 230 |
| LS-3.8 - LSG-10/3.8 | 49 | 56 | 60 | 76 | 85 | 98 | 118 | 136 |

Eurodrip

Damla Sulama Sistemleri

